



Order reference		SA-	AF	0			
Article number		8138	829				
Date	4-11-1	1		Replaces	04-03-08	No. Pages	1

Product Description:

Oil only kit consisting of one (1) adsorbent roll (76 cm x 46 m, perforated			
every 76 cm) and one (1) anti-fatigue base mat (82 cm x 152 cm)			
adsorbent roll (76 cm x 46 m, perforated every 76 cm),			
anti-fatigue base mat (82 cm x 152 cm)			
Adsorbent: white; base mat: black			
Adsorbent: 100% Polypropylene			
Base mat: 100% Nitrile rubber			
Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]			
Hydrophobic + Oleophilic			

Absorbency Capacity	187 l per roll (saturated; medium viscosity)

Packaging Description:

r achaging Description			
Package configuration	2 Case	Pkg. Weight	10.8 kg (10.2 kg)
			+ 13.9kg (13.8kg)
Items per Package	1 mat, 1 adsorbent roll	Pkg. Dimensions	20cm x 20cm x 95cm H + 49 cm x 49 cm x 105 cm H
Container type	Carton		

Physical Properties:

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	365	36
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency**	SPCTM-004B	gL/gS	12.5	2
(med.visc.)				
Tear Strength	SPCTM-006	daN	13.8	1.3
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling Each package to be clearly labeled with Company Name, Address, Ite	
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.